

# Package: mcmcensemble (via r-universe)

October 18, 2024

**Title** Ensemble Sampler for Affine-Invariant MCMC

**Version** 3.1.0.9000

**Description** Provides ensemble samplers for affine-invariant Monte Carlo Markov Chain, which allow a faster convergence for badly scaled estimation problems. Two samplers are proposed: the 'differential.evolution' sampler from ter Braak and Vrugt (2008) <[doi:10.1007/s11222-008-9104-9](https://doi.org/10.1007/s11222-008-9104-9)> and the 'stretch' sampler from Goodman and Weare (2010) <[doi:10.2140/camcos.2010.5.65](https://doi.org/10.2140/camcos.2010.5.65)>.

**License** GPL-2

**URL** <https://hugogruson.fr/mcmcensemble/>,  
<https://github.com/Bisaloo/mcmcensemble>

**BugReports** <https://github.com/Bisaloo/mcmcensemble/issues>

**Depends** R (>= 3.5)

**Imports** future.apply, progressr

**Suggests** bayesplot, coda, mockery, testthat (>= 3.0.0), knitr, rmarkdown

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.1

**Config/testthat/edition** 3

**Config/Needs/website** r-for-educators/flair, spacefillr

**VignetteBuilder** knitr

**Repository** <https://bisaloo.r-universe.dev>

**RemoteUrl** <https://github.com/bisaloo/mcmcensemble>

**RemoteRef** HEAD

**RemoteSha** 326a1a0718e65f210181e7b1a1f3435017765f33

## Contents

MCMCEnsemble . . . . .	2
<b>Index</b>	<b>5</b>

---

MCMCEnsemble	<i>MCMC ensemble sampler</i>
--------------	------------------------------

---

### Description

Ensemble Markov Chain Monte Carlo sampler with different strategies to generate proposals. Either the *stretch move* as proposed by Goodman and Weare (2010), or a *differential evolution jump move* similar to Braak and Vrugt (2008).

### Usage

```
MCMCEnsemble(
  f,
  inits,
  max.iter,
  n.walkers = 10 * ncol(inits),
  method = c("stretch", "differential.evolution"),
  coda = FALSE,
  ...
)
```

### Arguments

<code>f</code>	function that returns a single scalar value proportional to the log probability density to sample from.
<code>inits</code>	A matrix (or data.frame) containing the starting values for the walkers. Each column is a variable to estimate and each row is a walker
<code>max.iter</code>	maximum number of function evaluations
<code>n.walkers</code>	number of walkers (ensemble size). An integer greater or equal than 2.
<code>method</code>	method for proposal generation, either "stretch", or "differential.evolution". This argument will be saved as an attribute in the output (see examples).
<code>coda</code>	logical. Should the samples be returned as <code>coda::mcmc.list</code> object? (defaults to FALSE)
<code>...</code>	further arguments passed to <code>f</code>

### Value

- if `coda = FALSE` a list with:
  - *samples*: A three dimensional array of samples with dimensions walker x generation x parameter

- *log.p*: A matrix with the log density evaluate for each walker at each generation.
- if *coda* = TRUE a list with:
  - *samples*: A object of class `coda::mcmc.list` containing all samples.
  - *log.p*: A matrix with the log density evaluate for each walker at each generation.

In both cases, there is an additional attribute (accessible via `attr(res, "ensemble.sampler")`) recording which ensemble sampling algorithm was used.

## References

- ter Braak, C. J. F. and Vrugt, J. A. (2008) Differential Evolution Markov Chain with snooker updater and fewer chains. *Statistics and Computing*, 18(4), 435–446, doi:[10.1007/s11222008-91049](https://doi.org/10.1007/s11222008-91049)
- Goodman, J. and Weare, J. (2010) Ensemble samplers with affine invariance. *Communications in Applied Mathematics and Computational Science*, 5(1), 65–80, doi:[10.2140/camcos.2010.5.65](https://doi.org/10.2140/camcos.2010.5.65)

## Examples

```
## a log-pdf to sample from
p.log <- function(x) {
  B <- 0.03 # controls 'bananacity'
  -x[1]^2/200 - 1/2*(x[2]+B*x[1]^2-100*B)^2
}

## set options and starting point
n_walkers <- 10
unif_inits <- data.frame(
  "a" = runif(n_walkers, 0, 1),
  "b" = runif(n_walkers, 0, 1)
)

## use stretch move
res1 <- MCMCEnsemble(p.log, inits = unif_inits,
  max.iter = 300, n.walkers = n_walkers,
  method = "stretch")

attr(res1, "ensemble.sampler")

str(res1)

## use stretch move, return samples as 'coda' object
res2 <- MCMCEnsemble(p.log, inits = unif_inits,
  max.iter = 300, n.walkers = n_walkers,
  method = "stretch", coda = TRUE)

attr(res2, "ensemble.sampler")

summary(res2$samples)
plot(res2$samples)
```

```
## use different evolution move, return samples as 'coda' object
res3 <- MCMCEnsemble(p.log, inits = unif_inits,
                    max.iter = 300, n.walkers = n_walkers,
                    method = "differential.evolution", coda = TRUE)

attr(res3, "ensemble.sampler")

summary(res3$samples)
plot(res3$samples)
```

# Index

`coda::mcmc.list`, [2](#), [3](#)

`MCMCEnsemble`, [2](#)